



CONTROL YOUR COLLABORATION WITH EASE

BENEFITS

- Integrated calendar so it's easy to find your meeting and connect
- Intuitive interface makes it easy to personalize the experience for more productive meetings
- Power over Ethernet means only one cable is required, keeping your table clean
- Easy setup as it's pre-paired out of the box when purchasing as part of a full Poly video solution

POLY TC8

This intuitive touch interface provides easy access to Poly video conferencing solutions. The sleek design features an 8" high-resolution touch display to ensure that the control options are clear and accessible. A single cable carries both power and data to reduce clutter. After using the Poly TC8, you'll never stress about getting your meeting going again. Having confidence that you can easily initiate, join, or share content lets you focus on better collaboration.

- Integrated calendar for one touch to join a call
- Easily share content, adjust the camera, and change participant layouts
- Compatible with Poly Studio X family and Poly G7500

POLY TC8



SPECIFICATIONS

PACKAGE INCLUDES:

- Poly TC8 and RJ45 (LAN) cable
- Setup sheet
- Printed warranty statement

PHYSICAL CHARACTERISTICS

- Physical dimensions: 205 W x 123 H x 79 D mm (8.07" W x 4.84" H x 3.11" D in)
- Micro-B USB 2.0 (diagnostics)
- Mechanical locking mechanism (Kensington lock)
- Weight: 812 g (1.79 lb)

OPERATING ENVIRONMENT

- Temperature: 0 to 40 °C (32 - 104 °F)
- Non-operating: -20 to 60 °C (-20 - 140 °F)

ALTITUDE

- Operating: 0 to 10,000 ft ASL
- Non-operating: 0 to 35000 ft ASL

COMPATIBLE SYSTEMS

- Poly G7500 (min 3.0 software)
- Poly Studio X30 and Studio X50

USABILITY

- Display: 8-inch screen
- Aspect ratio: 16 x 10
- Resolution: WXGA (1280 x 800)
- Designed with built-in stand support—no external stand required

- Viewing angle: 178 degrees (U/D/L/R)
- Positioning/placing angle: 60 degrees
- Tap and touch control to access call controls and administrative menus
- Intuitive user interface

TECHNOLOGY

- Capacitive touch sensor supports multi-touch functionality
- Direct API command through network
- LCD panel with LED backlighting
- IPS (In-Plane Switching)
- Ultra Sonic Emitter (for auto pairing)

ELECTRICAL

- Power over Ethernet (PoE), compatible with IEEE 802.3af Class 3
- Low-power sleep mode

WARRANTY

- One-year return to factory parts and labor
- 90-day software warranty

PART NUMBER

- 2200-30760-001

LEARN MORE

For more information on Poly TC8 visit www.poly.com.