

Polycom® VSX™ 5000

Technical Specifications



Video Standards & Protocols

- H.261
- H.263++
- H.264
- People+Content / H.239
- H.263 and H.264 Video Error Concealment

People Video Resolution

- NTSC 30fps at 56Kbps-768Kbps
- PAL 25fps at 56Kbps-768Kbps
- Receives Polycom Pro-Motion™ 60/50 fields per second (full screen video for NTSC/PAL applications)
- 4SIF (704 x 480), 4CIF (704 x 576) *2nd video only
- SIF (352 x 240), CIF (352 x 288)
- QSIF (176 x 120), QCIF (176 x 144)
- Choice of 4:3 or 16:9 display aspect ratios

Content Video Resolution

- XGA (1024 x 768), SVGA (800 x 600), VGA (640 x 480)

Audio Standards & Protocols

- Polycom StereoSurround™
- 14kHz bandwidth with Polycom Siren 14, G.722.1 Annex C
- 7 kHz bandwidth with G.722, G.722.1
- 3.4 kHz bandwidth with G.711, G.728, G.729A
- Automatic Gain Control
- Automatic Noise Suppression
- Instant Adaptation Echo Cancellation
- Audio Error Concealment

Other ITU-Supported Standards

- H.221 communications
- H.224/H.281 far-end camera control
- H.323 Annex Q far-end camera control
- H.225, H.245, H.241
- H.231 in multipoint calls
- H.243 chair control
- H.460.18/19 NAT/firewall traversal
- BONDING, Mode 1

Network

- H.320 - Up to 512Kbps with optional QBRI
- H.323 up to 768Kbps
- SIP up to 768Kbps
- SCCP up to 768Kbps
- iPriority for QoS

User Interface

- COD (PathNavigator Conference on Demand)
- Embedded AES FIPS 197, H.235V3 and H.233/234
- Directory Services
- System Management
 - Web based
 - SNMP
 - ReadiManager SE200
- CDR
- API support
- Auto SPID detection and line number configuration
- International languages (16)

Security

- FIPS 140-2 Certified
- Secure web [HTTPS]
- Secure TLS in Web, Telnet, FTP
- Security mode
- Secure password authentication
- Embedded AES FIPS 197, H.235V3 and H.233/234
- Video Overlays

Electrical

- Auto sensing power supply
- Operating voltage/power 90-260 VAC, 47-63 Hz/80 Watts
- Max 75 VA@115v60Hz, 85 VA@220v50Hz
- Max Heat Dissipation; 273 BTU/hour

Environmental Specification

- Operating Temperature: 0-40°C
- Operating Humidity: 15-80%
- Non-Operating Humidity: -40-70° C
- Non-Operating Humidity (Non-condensing): 10-90%
- Maximum altitude is 10,000 feet

Physical Characteristics

- Video Base Unit (W/H/D): 11.83" / 5.25" / 10.02"; 300.3 mm / 133.26 mm / 254.5 mm
- Video Base Unit Weight: 4.4 lbs; 1.94 kg

Warranty

- One-year return to factory parts and labor
- 90-day software warranty

Options


- QBRI module for ISDN capability up to 512Kbps
- Second Monitor Adaptor key for dual monitor functionality
- Visual Concert VSX, PC/MAC compatible
 - Video input to codec, HD-15 connector
 - Audio input to codec, 3.5mm connector
 - Video output from codec, conference or local content, HD-15 connector
 - LAN hub, 1 input from LAN, 3 PC connections
- Cable-free content sharing with People+Content IP
- SoundStation VTX 1000

Polycom Moscow 


zakaz@polycom-moscow.ru

T +7 95-924-25-25

www.polycom-moscow.ru



Electronic PTZ camera with Privacy Shutter



IR receiver

- | | | |
|--|---|--|
| 1. Video input 1 for VCR/DVD | 5. Audio input 1 (main): support one device for stereo audio – see admin manual for device options and correct ordering of devices. | 8. RS-232 for control, pass thru, vertical solutions |
| 2. Video output 1 for main monitor | 6. Audio input 2 for stereo (VCR/DVD) | 9. LAN NIC, 10/100 auto sensing |
| 3. Video output 2 for VGA/XGA main monitor, optional VGA/XGA 2 nd monitor | 7. Audio output for stereo (line level) | 10. Power and H.320 Quad ISDN BRI S/T-interface connection |
| 4. Video output 3 for optional 2 nd monitor | | 11. Kensington™ lock connection |